

Engelmann **Ultrasonic Thermal Energy Meter**

SensoStar **U / UC**

Ultrasonic flow sensor for inline installation points



Most accurate measurement results
in any installation position

Various installation options due to a large selection
of installation lengths

Flexible communication based on modular system

Fast response due to dynamic temperature
measurement cycle



Precise heat/cooling measurement via ultrasound

The **SensoStar U** and **SensoStar UC** are high-precision measuring devices that use ultrasonic measurement technology to record heat or cooling energy. Whether in brass or composite version – this meter offers the right solution for every installation situation and every requirement. The comprehensive range covers all installation lengths, temperature sensor and communication variants.

We speak your language

The continuously growing portfolio of communication modules offers you a wide range of remote readout options.





RADIO MODULES



Features & Range of Functions

- Sizes: DN 15 to DN 50
- Meters from Qp 0.6 to Qp 15
- Lengths: 105 mm to 300 mm
- Horizontal / vertical / overhead installation
- Installation point and display unit adjustable on site
- Return flow and air detection
- Detachable calculator with 0.85 m or 2.85 m connection cable
- Battery capacity of up to 20 years

WIRED MODULES



wM-Bus, LoRaWAN and M-Bus can also be equipped with 3 pulse inputs to connect other devices.

Calculator

Temperature range medium	°C	0 – 150 heat / 0 – 50 cooling
Ambient temperature in the field	°C	5 – 55 at 95 % relative humidity
Transport temperature	°C	-25 – 70 (for max. 168 h)
Storage temperature	°C	-25 – 55
Temperature difference range $\Delta\theta$ heat	K	3 – 100
Temperature difference range $\Delta\theta$ cooling	K	-3 – -50
Minimum temperature difference $\Delta\theta$ heat	K	> 0.05
Minimum temperature difference $\Delta\theta$ cooling	K	<-0.05
Minimum temperature difference $\Delta\theta$ heat/cooling	K	> 0.5 / <-0.5
Resolution temperature	°C	0.01
Measuring cycle temperature; dynamic	s	2 / 60; by using external power supply: 2 s permanent
Measuring cycle flow	s	2
Calculator housing dimensions (H x W x D)	mm	75 x 110 x 34.5
Length of connecting cable calculator-flow sensor	m	0.85 (optional: 2.85)
Display		LCD – 8 digits + special characters
Displayed thermal energy		up to 3 decimal places
Units		MWh, kW, m³, m³/h (kWh, GJ, MMBTU, Gcal) unit of energy can be set when the amount of energy is still ≤ 10 kWh
Interfaces		optical interface (M-Bus protocol) <i>optional communication:</i> radio: wireless M-Bus*, LoRaWAN* wired: M-Bus*, Modbus, 2 pulse outputs
Power supply		easily replaceable 3 V lithium battery preparation for 3 V power pack available (input voltage 230V / 24V)
Battery capacity, designed	years	20 (without communication module) 16 (M-Bus, readout interval 1 hour) 15 (M-Bus, readout interval 10 minutes) 10 (with others e.g. wM-Bus, Modbus, LoRaWAN)
Data storage		24 monthly and semi-monthly values
Billing dates		freely selectable annual billing date 15 monthly and semi-monthly values via display or radio (compact mode) 24 monthly and semi-monthly values via optical interface or M-Bus
2 tariff registers		individually adjustable; store energy or time
Storage of the maximum values		flow, power and temperatures (inlet, outlet, $\Delta\theta$) as well as the respective maximum values of the last 15 months
Protection class		IP65
Approvals		DE-16-MI004-PTB025; DE-16-M-PTB-0097 CH-T2-18768-00 CE
Type designation		S3
EMC (MID)		EN 1434

* Optional with 3 pulse inputs.

SensoStar U / SensoStar UC

TECHNICAL DATA

Flow sensors (general)		
Measuring method		ultrasound; time-of-flight
Accuracy class (MID)		class 2
Protection class		IP68
Nominal pressure PN	bar	16
Medium		water
Mounting position		any position (horizontal, vertical, overhead)
Point of installation		outlet flow and inlet flow; can be set when the amount of energy is still ≤ 10 kWh
Temperature range medium heat	°C	15 – 90 15 – 130 high temperature (150; for max. 2000 h) (optional)
Temperature range medium cooling (from Qp 0.6 to Qp 15)	°C	5 – 50
Temperature range medium heat/cooling	°C	15 – 90 heat 15 – 120 high temperature (optional) 5 – 50 cooling

Temperature sensors (2-wire technology)		
Platinum precision resistor Pt 1000 (soldered in place)		
Sensor diameter	mm	UTS: 5; 5.2; 6; AGFW: 27.5; 38
Connection cable length	m	1.5; 3; 6
Installation type		asymmetrical; symmetrical
Platinum precision resistor Pt 500 (interchangeable in pairs)		
Sensor diameter	mm	UTS: 5; 5.2
Connection cable length	m	1.5; 3
Installation type		asymmetrical; symmetrical

SensoStar U / SensoStar UC

TECHNICAL DATA


Flow sensor brass														
Sizes	Nominal flow rate Qp	m³/h	0.6	0.6	1.5	1.5	2.5	2.5	3.5	3.5	6	6	10	15
	Low flow threshold value	l/h	6	6	6	6	12	12	14	14	30	30	50	50
	Minimum flow Qi	l/h	12	12	12	12	25	25	28	28	60	60	100	150
	Maximum flow Qs	m³/h	1.2	1.2	3	3	5	5	7	7	12	12	20	30
Pressure drop Δp at Qp		bar	0.03	0.03	0.21	0.04	0.12	0.12	0.21	0.21	0.20	0.20	0.11	0.14
Pressure drop Δp at Qs		bar	0.13	0.13	0.85	0.17	0.46	0.46	0.89	0.89	0.80	0.80	0.43	0.71
Nominal diameter		mm	DN 15	DN 20	DN 15	DN 20	DN 20	DN 25	DN 20	DN 25	DN 25	DN 32	DN 40	DN 50
Dynamic range Qi/Qp		-	1:50	1:50	1:125	1:125	1:100	1:100	1:125	1:125	1:100	1:100	1:100	1:100

Meter dimensions brass						
Qp (m³/h)	Nominal diameter	G (") F (mm)	L (mm)	H (mm)	A (mm)	Weight standard version (kg)
0.6	DN 15	G3/4B	110	65	38.5	0.600
0.6	DN 20	G1B	190	65	38.5	0.770
1.5	DN 15	G3/4B	110	65	38.5	0.600
1.5	DN 20	G1B	105	66	39.5	0.650
1.5	DN 20	G1B	130	66	39.5	0.680
1.5	DN 20	G1B	190	65	38.5	0.770
2.5	DN 20	G1B	105	66	39.5	0.650
2.5	DN 20	G1B	130	66	39.5	0.680
2.5	DN 20	G1B	190	66	39.5	0.790
2.5	DN 25	G1 1/4B	260	66	39.5	1.080
3.5	DN 20	G1B	130	66	39.5	0.680
3.5	DN 20	G1B	190	66	39.5	0.790
3.5	DN 25	G1 1/4B	150	66	39.5	0.820
3.5	DN 25	G1 1/4B	260	66	39.5	1.080
6.0	DN 25	G1 1/4B	150	68.5	42	0.820
6.0	DN 25	G1 1/4B	260	68.5	42	1.080
6.0	DN 32	G1 1/2B	150	68.5	42	1.020
6.0	DN 32	G1 1/2B	260	68.5	42	1.330
10.0	DN 40	G2B	200	73	46.5	1.530
10.0	DN 40	G2B	300	73	46.5	1.970
15.0	DN 50	F 128.4	200	73.7	44.9	4.600
15.0	DN 50	F 128.4	270	73.7	44.9	4.950



SensoStar U / SensoStar UC

TECHNICAL DATA

SENSOSTAR U (QP 0.6 – QP 10)




SENSOSTAR U flange (QP 15)



SensoStar U / SensoStar UC

TECHNICAL DATA

PRESSURE DROP SENSOSTAR U




SensoStar U / SensoStar UC

TECHNICAL DATA

Flow sensor composite				
Sizes	Nominal flow rate Qp	m³/h	0.6	1.5
	Low flow threshold value	l/h	6	6
	Minimum flow Qi	l/h	12	12
	Maximum flow Qs	m³/h	1.2	3
Pressure drop Δp at Qp		bar	0.05	0.16
Pressure drop Δp at Qs		bar	0.11	0.68
Nominal diameter		mm	DN 15	DN 15
Dynamic range Qi/Qp		-	1:50	1:125

Meter dimensions composite						
Qp (m³/h)	Nominal diameter	G (")	L (mm)	H (mm)	A (mm)	Weight standard version (kg)
0.6	DN 15	G3/4B	110	58	38.5	0.260
1.5	DN 15	G3/4B	110	58	38.5	0.260


SENSOSTAR UC



SensoStar U / SensoStar UC

TECHNICAL DATA

PRESSURE DROP SENSOSTAR U



Contact us here:



+49 6222 98 00 188 (Orders)
+49 6222 98 00 2727 (Technical Service)
+49 6222 98 00 0 (Head Office)



info@engelmann.de



Engelmann Sensor GmbH
Rudolf-Diesel-Straße 24-28
69168 Wiesloch-Baiertal
Germany



www.engelmann.de