

Engelmann Heat Meter Calculator

SensoStar C



Various application options due to a large selection of variants and setting options

User-friendly mounting system for easy connection of flow and temperature sensors

Flexible communication based on a modular system

Connection of an external power pack enables direct monitoring of your system



Precise heat/cooling measurement

The **SensoStar C** is a flexible calculator for recording heat or cooling energy that offers a suitable solution for every installation situation. Specially designed for the measurement of large volume flows, the calculator can be easily combined with all standard flow sensors. The range is rounded off by a wide selection of retrofittable communication modules as well as the option of an external power pack for direct system monitoring.

We speak your language

The continuously growing portfolio of communication modules offers you a wide range of remote readout options.





RADIO MODULES



Features & Range of Functions

- Available for heating and cooling applications
- Wide range of variants for different requirements
- Installation point and display unit adjustable on site
- Battery capacity of up to 20 years
- Automatic adjustment of the temperature measurement cycle by using external power supply

WIRED MODULES



wM-Bus, LoRaWAN and M-Bus can also be equipped with 3 pulse inputs to connect other devices.

General

Environmental class (MID)	C (EN 1434)
Mechanical class (MID)	M2
Electromagnetic class (MID)	E2

Calculator

Temperature range medium	°C	0 – 150 heat / 0 – 50 cooling
Ambient temperature in the field	°C	5 – 55 at 95 % relative humidity
Transport temperature	°C	-25 – 70 (for max. 168 h)
Storage temperature	°C	-25 – 55
Temperature difference range $\Delta\theta$ heat	K	3 – 100
Temperature difference range $\Delta\theta$ cooling	K	-3 – -50
Minimum temperature difference $\Delta\theta$ heat	K	> 0.05
Minimum temperature difference $\Delta\theta$ cooling	K	<-0.05
Minimum temperature difference $\Delta\theta$ heat/cooling	K	> 0.5 / <-0.5
Resolution temperature	°C	0.01
Temperature measurement cycle in normal operation	s	30 (Germany) 60 (international) 2 by using a power pack
Pulse values, optional	l/pulse	1; 2.5; 10; 25; 100; 250; 1000; 2500
Display		LCD – 8 digits + special characters
Displayed thermal energy		up to 3 decimal places
Units		MWh, kW, m ³ , m ³ /h (kWh, GJ, MMBTU, Gcal) unit of energy can be set when the amount of energy is still \leq 10 kWh
Interfaces		optical interface (M-Bus protocol, ZVEI according to EN 62056-21) <i>optional communication:</i> radio: wireless M-Bus,* LoRaWAN* wired: M-Bus,* Modbus RTU, 2 pulse outputs * Optional with 3 pulse inputs.
Power supply		easily replaceable 3 V lithium battery (A-cell, 0.86 g lithium) preparation for 3 V power pack available (input voltage 230 V / 24 V)
Battery capacity, estimated	years	20 (without communication module) 16 (M-Bus, readout interval 1 hour) 15 (M-Bus, readout interval 10 minutes) 10 (with others, e.g., wM-Bus, Modbus RTU, LoRaWAN)
Data storage		24 monthly and 24 semi-monthly values
Billing dates		freely selectable annual billing date 15 monthly and 15 semi-monthly values via display 15 monthly via radio 24 monthly and 24 semi-monthly values via optical interface or M-Bus
2 tariff registers		individually adjustable; store energy or time
Storage of the maximum values		flow, power and temperatures (inlet, outlet, $\Delta\theta$) as well as the respective maximum values of the last 15 months
Protection class		IP54
Approvals		DE-18-MI004-PTB037; DE-18-M-PTB-0049 CH-T2-18769-00 CE
Type designation		S3
Pulse input device		microcontroller CMOS input of class IB according to EN 1434-2:2015 (D)
Medium		water; optional, without approval: water with a propylene glycol or ethylene glycol percentage rate of 20 %, 30 %, 40 % or 50 % (type and concentration of glycol can be set at any time)
Weight	kg	0.350
W x H x D	mm	150 x 130 x 35

Flow sensor requirements

Encoder type class (according to EN 1434-2:2015)		OA (reed contact); OC (open collector)
Maximum input frequency	Hz	10
Pulse length	ms	at least 25
Pulse pause	ms	at least 50

Temperature sensor requirements

Platinum precision resistor		Pt 500
Connecting cable length (unshielded)	m	up to 10 m in 2-wire technology (3 and 10 available at Engelmann)
Installation type		direct immersion; in thermowells



Contact us here:



+49 6222 98 00 188 (Orders)
+49 6222 98 00 2727 (Technical Service)
+49 6222 98 00 0 (Head Office)



info@engelmann.de



Engelmann Sensor GmbH
Rudolf-Diesel-Straße 24-28
69168 Wiesloch-Baiertal
Germany



www.engelmann.de